


MAZDA

Back-lit panel

RC007C



220V
240V

50Hz
60Hz



Max.
45 °C
Min.
-10 °C

GLOW
WIRE
650 °C



Lumen (lm) CCT (K) P(W) L xW xH (mm)

MAZDA RC007C LED32S/840 PSU W60L60 OC FR 3200 4000 36 595 x 595 x 35 2

Available as accessory


Suspension set:
RC007Z SME-2
911401824280



4x


8x ST3.2

6x Ø 6 / 6x ST4



2x

Surface mounted set:
RC132C SMB W60L60
910930031018



2x

2x

4x

4x


Plaster set:
RC007Z SMB-PLC
911401824180



4x

8x ST3.2

Safety cable:
RC065Z SC
911401892680



2x

2x

1x



4x ST3.2



1x



VPC visible profile ceiling



The luminaire shall, under no circumstance, be covered with thermal insulation matting or similar material.




If the external flexible cable or cord of this luminaire is damaged, it shall be exclusively replaced by the manufacturer or his service agent or a similar qualified person in order to avoid a hazard.

The light source contained in this luminaire shall only be replaced by the manufacturer or his service agent or a similar qualified person.


Luminaire must not be used or stored in corrosive environment where hazardous materials such as sulphur, chlorine, phthalates, etc, are present.

Inrush current



Electrical characteristics



I _{max} (A)	15
T _{ref} (μs)	200
MCB	Luminaires Max.
B-10 A	22
B-13 A	29
B-16 A	35
C-10 A	36
C-13 A	47
C-16 A	59



A Visible Profile Ceiling mounting(VPC)





Install safety cable
(Optional)




B Suspension mounting (SUS)

Dimensions in mm





Replace the bracket with
the bracket in the suspension set.




C Plaster Ceiling Version mounting (PCV)



Install safety cable
(Optional)



D Safety cable



safety cable included in the box.

